



55000 4-Stroke Motorcycle Oil 15W-50 Premium Synthetic Ester

Document version: November 29th 2017



Description

This SAE 15W-50 fully synthetic ester based 4-stroke motorcycle oil is suitable for air or water-cooled 4-stroke competition engines. Due to its high specification ester blend, it allows the engine to perform highly not only at very high speed, but under very heavy load conditions also. The exceptional anti-wear/anti-friction additive combination not only enhances performance, but the high lubricity effect of the blend also reduces oil consumption and extends engine lifetime. This multi-functional MPM SAE 15W-50 engine oil is not only developed for road and race engines, but it is also suitable for less heavy duty day to day motorcycle engines. Note: This product is suitable for lubrication of gearboxes with or without wet clutches.

According to the specifications of

API SL
JASO MA / MA2

Packing units

ART. NO.	VOLUME	ITEMS PER UNIT	ITEMS PER PALLET
55001	1 L	6	450
55020	20 L	1	30
55060	60 L	1	12
55205	205 L	1	2
55999	1000 L	1	-
P55000	bulk	1	-

Typical characteristics

TEST	VALUE	
SAE	15W-50	
Density at 15°C	0,854	kg/l
Kinematic viscosity at 40°C	124	mm ² /s
Kinematic viscosity at 100°C	18	mm ² /s
Viscosity index	162	
Flashpoint COC	260	°C
Pourpoint	-36	°C
Total Base number	6,6	mgKOH/g