



BLO01000BIO Marine TC-W3 Oil 2-Stroke High Performance Biodegradable

Document version: November 29th 2017



Description

This marine TC-W3 Oil 2-stroke biolube is a full synthetic biodegradable 2-stroke oil for use in water-cooled outboard engines of watercrafts, jet skis and Evinrude E-TEC engines. This thermally stable oil ensures outstanding piston cleanliness and protection against rust.

The biodegradable 2-stroke oil is readily miscible with gasoline and suitable as self-mixing or in oil injection systems.

The mixing ratio of the oil is 2% (1:50) and 1% (1:100) in accordance with the recommendation with the engine manufacturer.

According to the specifications of

API TC+
CEC L-33-T-82 > 80%
NMMA TC-W3

Packing units

ART. NO.	VOLUME	ITEMS PER UNIT	ITEMS PER PALLET
BL001001BIO	1 L	6	450
BL001005BIO	5 L	4	112
BL001020BIO	20 L	1	30
BL001060BIO	60 L	1	12
BL001205BIO	205 L	1	2
BL001999BIO	1000 L	1	-
PBL001000BIO	bulk	1	-

Typical characteristics

TEST	VALUE	
Density at 15°C	0,897	kg/l
Colour	green	
Kinematic viscosity at 40°C	47	mm ² /s
Kinematic viscosity at 100°C	8,5	mm ² /s
Viscosity index	170	
Flashpoint COC	105	°C
Pourpoint	-36	°C
Total Base number	9,6	mgKOH/g